

Joey Micro9

Fully customizable wall mounted 9 button control system with LEDs. Controls IR and RS232 using the supplied Access Port breakout box. Simple CAT5 to RJ45 connection. Includes Power Supply.



A new concept in inexpensive, flexible control systems, Joey Micro9 is a 9 button fully programmable control system that will fit in a standard single gang wallbox. You can create button actions and controls using the same simple authoring software as the rest of the Joey range.

Joey Micro will save you money by managing your equipment. Joey Micro is smart enough to know when a room is empty and will shut the room down. Especially important where projectors are installed. The Joey Micro does this by tracking time, key presses and room movement.

To customise a Joey Micro9 to suit your application, you design your own layout in landscape or portrait orientation using the simple drag and drop style Joey authoring program. Print the result on a colour printer onto high res paper cut it out and install it under the high gloss clip-on Perspex cover.

Joey Micro9 can directly control your equipment via Infra Red and RS232.

This allows Joey Micro to be a complete control solution, with far more functionality than you might assume from just 9 buttons, because they are context sensitive. LEDs on each button can be programmed to indicate the mode your system is in.

For more demanding applications, Joey Micro9 also directly interfaces to all processors in the CommBox range with full feedback support

| | |
|--------------------------------------|--|
| Enclosure | Standard single-gang HPM wallpl |
| Power Supply | 12v DC at 10mA (typ.) from IRBu |
| Dimensions | 110mm(H) x 67mm(W) x 10mm(L |
| Weight | 74g |
| Software | Joey Authoring Program |
| Connectivity | Connects to Access Port Via sing |
| Programming port (3.5mm Jack) | X 1 |
| IR Bus Phoenix Connector | X 1 |
| Compatibility | All IR formats supported by TCS. IRBus |
| Cut Out Dimensions | As standard single gang wall box |
| Depth above mounting plane | 12mm approx |
| Dimensions Access Port | 110mm(H) x 67mm(W) x 25mm(L wallplate) |
| Number of programmable keys | 9 per "virtual screen" |
| Number of virtual screens | 100 to 300 depending on applicat |
| E2 memory | 32 kb |
| Number of loadable codesets | 125 |